

3.2.1 - Choice of the transom in relation to load

Tab. 23 - Capacity of standard transom

belt width	type of transom and diameter of suitable rollers											
	A2 S-20° 	A3 L-30° 	A3 M-30° 	A3P-30° 				A3 S-35° 			R2 S-10° 	R2 SP 
	Ø 60÷110	Ø 76÷110	Ø 89÷110	Ø 110÷110	Ø 89÷108	Ø 108÷133	Ø 133÷159	Ø 133	Ø 159	Ø 194	Ø 89÷180	Ø 133÷194
mm	Kg											
300	338											
400	286	286										
500	205	247	247	247								
650	167	205	205	205							354	
			354	354								
800	167	167	289	289	289	289	289	289	289		289	
			460	460	460	460	460	460	460			
1000			244	244	244	244	244	244				
			388	388	388	388	388	388	388		388	
						581	581	581	581			
1200			204	204	204	204	204	204				
			325	325	325	325	325	325	325		325	
						487	487	487	487			
								634	634			
1400						288	288	431	431		431	
						431	431	561	561		561	
						561	561	710	710			
1600						387	387	387	387		387	
						503	503	503	503	503	503	
								637	637	753		
1800							446	446	446	446	342	
							667	667	667	667	446	446
2000									604	604	604	604
									909	909		
2200									558	558		840
									840	840		